


ゴムスポンジ

NRタイプ



N-145



N-146



N-147



N-148



N-155 (緑)



NBR-4112

CRタイプ



C-4205



C-4305




C-4315 (灰)



C-4405



C-4505 (硬質)




C-4555 (硬質)




C-4255 (導電性)




C-4266 (低硫黄タイプ)



C-4310 (白)



TT-4101 (シリコンスポンジ)



TL-4400 (シリコンスポンジ長尺品)




E-8000 (EPDM+シリルケラクス)


EPDMタイプ



E-4188



E-4388



E-4088 (特寸品)




E-4390 (白)




E-4108 (灰)



E-4488 (硬質)



E-4382 (ノンハロ難燃)



E-4385 (導電性)



E-4338 (低硫黄ノンハロ難燃)

製品仕様

タイプ	密度 (g/m ³)	硬度(度)	原反寸法(mm)	備考
N-145	0.180±0.03	20±5	30×1000×1000 30×1000×1500	黒
N-146	0.150±0.03	30±5	25×1000×1300 30×1000×1000	黒
N-147	0.170±0.03	33±5	30×1000×1000	黒
N-148	0.150±0.03	15±5	25×1000×1300	黒
N-155	0.190±0.03	30±5	25×1000×1000	緑
NBR-4112	0.150±0.03	15±5	30×1000×1000	黒
C-4205	0.180±0.03	10±5	30×1000×1000	黒・UL94HF-1
C-4305	0.190±0.03	25±5	30×1000×1000 30×1000×1300 30×1000×2000	黒・UL94HF-1
C-4315	0.190±0.03	20±5	30×1000×1000	灰・UL94HF-1
C-4405	0.200±0.03	25±5	30×1000×1000	黒・UL94HF-1
C-4505	0.250±0.03	35±5	20×1000×1000	黒・UL94HF-1
C-4555	0.250±0.03	50±5	30×1000×1000	黒
C-4255	0.190±0.03	15±5	30×1000×1000	黒・導電性・UL94HF-1
C-4266	0.200±0.03	22±5	30×1000×1000	黒・低硫黄・UL94HF-1
C-4310	0.220±0.03	23±5	30×1000×1000	白
TT-4101	0.250±0.05	10±5	22×500×1000	オレンジ
TL-4400	0.260±0.05		1~5 500×10m	白・UL94VO
E-8000	0.100±0.03		30×500×2000	黒
E-4188	0.120±0.03	10±5	30×1000×1000	黒
E-4388	0.150±0.03	20±5	30×1000×1000 30×1000×1300	黒
E-4088	0.100±0.03	7±5	33×1000×1300 30×1000×2000	黒
E-4390	0.170±0.03	20±5	30×1000×1000	白
E-4108	0.150±0.03	15±5	30×1000×1000	灰
E-4488	0.180±0.03	35±5	30×1000×1000	黒
E-4382	0.160±0.03	20±5	30×1000×1000	黒・難燃
E-4385	0.120±0.03	25±5	30×1000×1000	黒・導電性
E-4338	0.150±0.03	20±5	30×1000×1000	黒・低硫黄難燃